

QUADRANT		5300 RF	5300 RC	5300 FC	5300 SPECIAL CUT
Hitching					
PTO shaft speed	rpm	1000	1000	1000	1000
Hydraulic jack		●	●	●	●
Ball hitch		○	○	○	○
Hydraulic connection		2 single-acting and 1 open return line	2 single-acting and 1 open return line	2 single-acting and 1 open return line	2 single-acting and 1 open return line
Pick-up					
Width	m	2.35	2.35	2.35	2.35
DIN rake width	m	2.15	2.15	2.15	2.15
Number of tine bars		4	4	4	4
Two oscillating pick-up castor guide wheels		●	●	●	●
POWER FEEDING SYSTEM (PFS)		○	○	○	○
Hydraulically driven PFS		○	○	○	○
Crop feed					
Rotor		ROTO FEED	ROTO CUT	FINE CUT	RF/RC/FC
Number of knives		–	25	51	180
Blanked-off knives		–	●	●	–
Knife group changing		–	25, 13, 12, 6, 0	51, 26, 13, 12, 0/ 51, 26, 25, 13, 0	51, 26, 13, 12, 0
Knife drawer		–	●	●	●
Phase packer tines		2 (●)	2 (●)	2 (●)	2 (●)
Adjustable hydraulic pre-chamber		●	●	●	●
Fixed-cycle pre-chamber		–	–	–	–
Bale chamber					
Ram strokes	rpm	46	46	46	46
Max. baling pressure	bar	200	200	200	200
Automatic baling pressure control		●	●	●	●
Bale ejector		●	●	●	●
Bale deposit sensor		○	○	○	○
Moisture sensor		○	○	○	○
Bale chamber dimensions					
Length	m	3.85	3.85	3.85	3.85
Width	m	1.20	1.20	1.20	1.20
Height	m	0.90	0.90	0.90	0.90
Bale length	m	0.50–3.00	0.50–3.00	0.50–3.00	0.50–3.00
Operation					
CLAAS COMMUNICATOR II		●	●	●	●
OPERATOR		○	○	○	○
ISOBUS cable		○	○	○	○
EASY on board		○	○	○	○
Automatic central lubrication		●	●	●	●
Manual central lubrication		–	–	–	–
LED package		○	○	○	○
Bale weighing system		○	○	○	○
Wrapping					
Number of knotters		6	6	6	6
Knotter monitoring		○	○	○	○
Number of twine reels in air diffuser		24 x 11.5 kg	24 x 11.5 kg	24 x 11.5 kg	24 x 11.5 kg
TURBO FAN knotter cleaning system with air diffuser		●	●	●	●
HIGH SPEED BINDING		●	●	●	●
Bale drop onto field					
Depositing chute, mechanically folding		●	●	●	●
Depositing chute, hydraulically folding		○	○	○	○
Hydraulically folding roller bale chute		○	○	○	○
Dimensions and weights					
Width		2.78–2.99	2.78–2.99	2.78–2.99	2.78–2.99
Height		3.37–3.56	3.37–3.57	3.37–3.57	3.37–3.57
Length in transport position		8.86	8.86	8.86	9.98
Length in working position		9.86	9.86	9.86	10.85
Weight (with tandem axle)		10510	12120	12240	13440

5200 RF	5200 FC	5200 SPECIAL CUT	4200 RF	4200 RC	4200 SPECIAL CUT
1000	1000	1000	1000	1000	1000
●	●	●	●	●	●
○	○	○	○	○	○
2 single-acting and 1 open return line	2 single-acting and 1 open return line	2 single-acting and 1 open return line	2 single-acting and 1 open return line	2 single-acting and 1 open return line	2 single-acting and 1 open return line
2.35	2.35	2.35	2.35	2.35	2.35
2.15	2.15	2.15	2.15	2.15	2.15
4	4	4	4	4	4
●	●	●	●	●	●
○	●	●	○	○	○
○	○	○	○	○	○
ROTO FEED	FINE CUT	RF/RC/FC	ROTO FEED	ROTO CUT	RF/RC
–	51	180	–	25	180
–	●	–	–	○	–
–	51, 26, 13, 12, 0/ 51, 26, 25, 13, 0	51, 26, 25, 13, 0	–	25, 13, 12, 0	–
–	●	–	–	●	–
2 (●)	2 (●)	2 (●)	3 (●)	3 (●)	3 (●)
●	●	●	–	–	–
–	–	–	●	●	●
56	56	56	51	51	51
200	200	200	200	200	200
●	●	●	○	○	○
●	●	●	○	○	○
○	○	○	○	○	○
●	○	○	○	○	○
3.85	3.85	3.85	3.45	3.45	3.45
1.2	1.20	1.20	1.20	1.20	1.20
0.7	0.70	0.70	0.70	0.70	0.70
0.50–3.00	0.50–3.00	0.50–3.00	0.50–3.00	0.50–3.00	0.50–3.00
●	●	●	○	○	○
○	○	○	○	○	○
○	○	○	○	○	○
○	○	○	○	○	○
○	○	○	○	○	○
○	○	○	○	○	○
6	6	6	6	6	6
○	○	○	○	○	○
24 x 11.5 kg	24 x 11.5 kg	24 x 11.5 kg	24 x 11.5 kg	24 x 11.5 kg	24 x 11.5 kg
●	●	●	●	●	●
–	–	–	–	–	–
●	●	●	●	●	●
○	○	○	○	○	○
○	○	○	○	○	○
2.52–2.97	2.52–2.97	2.52–2.97	2.52–2.96	2.52–2.96	2.52–2.96
2.55–2.65	3.11–3.16	3.11–3.16	3.14–3.16	3.14–3.16	3.14–3.16
8.1	8.1	8.1	8.1	8.1	8.1
9.32	9.32	9.32	9.32	9.32	9.32
8120	9850	11050	7450	7800	9760

● Standard ○ Optional – Unavailable

CLAAS continually develops its products to meet customer requirements. This means that all products are subject to change without notice. All descriptions and specifications in this brochure should be considered approximate and may include optional equipment that is not part of the standard specifications. This brochure is designed for worldwide use. Please refer to your nearest CLAAS dealer and their price list for local specification details. Some protective panels may have been removed for photographic purposes in order to present the function clearly. To avoid any risk of danger, never remove these protective panels yourself. In this respect, please refer to the relevant instructions in the operator's manual.